



Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.

Data			
Adhesion	High initial tack and does not roll off too lightly		
Sound	Low-noise		
Warranty	Positive printing	6 months	
	All-over diapositive printed / coloured	Due to risk of tearing warranty can not be given	
Recommended max. width printing	Tape width minus 3 mm		
Colours	Brown, white		
Number of colours printed	Max. 3 colours		
Core diameter	76 mm		
Minimum order (50 mm x 50 mtr)	3 boxes = 108 rolls		

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours	
				19	25	30	38	50	75	-	150			200
Paper				19									500 mtr	3

Application

Paper 135 μ is a self-adhesive packaging tape with a high tensile strength suitable for printing. The special adhesive and the thick backing material will ensure a reliable sealing of heavy cartons and pack lots.

Technical Data	Unit	
Base		Paper
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 35
Paper thickness	μm	± 100
Adhesive thickness	μm	35
Total thickness	μm	± 135
Adhesion Strength	N/cm	$2.5 \pm 10\%$

Properties

- high tensile strength and adhesion strength
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature
- suitable for printing
- environmentally friendly, recyclable with cardboard
- possibility for nylon reinforced

Storage conditions

Store in a clean dry place. Temperature 15 - 25 degrees celcius.