

Adhesive paper 135 μ Reinforced with nylon wires

Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.

Reinforced with 3 nylon wires: - 2x length
- 1x sinus

| Data | | |
|---------------------------------|---|--|
| Adhesion | High initial tack and does not roll off too lightly | |
| Sound | Low-noise | |
| Warranty | Positive printing | 6 months |
| | All-over diapositive printed / coloured | Due to risk of tearing warranty can not be given |
| Recommended max. width printing | Tape width minus 3 mm | |
| Colours | Brown, white | |
| Number of colours printed | Max. 3 colours | |
| Core diameter | 76 mm | |
| Minimum order (50 mm x 50 mtr) | 3 boxes = 108 rolls | |

| Tape material | Tapewidth in mm. From ■ in maximum length possible | | | | | | | | | | | Max. length | Max. number of colours | |
|---------------|--|--|--|--|----|----|----|----|----|---|-----|-------------|------------------------|---|
| | | | | | | | | | | | | | | |
| Paper | | | | | 25 | 30 | 38 | 50 | 75 | - | 150 | 200 | 150 mtr | 3 |

Adhesive paper 135 μ Reinforced with nylon wires

Application

Paper 135 μ is a self-adhesive packaging tape with a high tensile strength suitable for printing. The special adhesive and the thick backing material will ensure a reliable sealing of heavy cartons and pack lots.

| Technical Data | Unit | |
|--------------------|---------------|----------------|
| Base | | Paper |
| Adhesive | | Natural rubber |
| Breaking Load | N/cm | minimum 43 |
| Paper thickness | μm | ± 100 |
| Adhesive thickness | μm | 35 |
| Total thickness | μm | ± 135 |
| Adhesion Strength | N/cm | $2.5 \pm 10\%$ |

Properties

- high tensile strength and adhesion strength
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature
- suitable for printing
- environmentally friendly, recyclable with cardboard
- possibility for nylon reinforced

Storage conditions

Store in a clean dry place. Temperature 15 - 25 degrees celcius.