



Characteristics

Closes boxes properly and then they can easily be opened without using sharp objects. Therefore much less risk of injury and damage. Saves time, for example on repacking. Low initial tack, full adhesion achieved after 24 hours. Print 6-8 months preservable. Suitable for frozen food packaging as long as processed above 0°C.

Data	
Adhesion	Low initial tack, full adhesion achieved after 24 hours
Sound	Low-noise
Warranty	1 year
Max. width printing	Tape width minus 2 mm
Colours	Clear, white, brown*
Number of colours printed	Up to 3 colours
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	4 boxes = 144 rolls

* Other colours on request





Application

Technical Data	Unit	
Base		Polypropylene film, biaxially oriented
Adhesive		Acrylic water-based
Elongation	%	150 ± 10%
Thickness	µm	54 ± 10%
Adhesion to steel	N/cm	2.4 ±10%
Tensile strenght	N/cm	51 ± 10%
Thickness foil	µ	32

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%

