



## Characteristics + Application

Strapping tape is a tear-resistant strapping tape with a coloured film for a permanent closure of medium heavy to heavy cartons, palletising, strapping and bundling.

Data	
Adhesion	High adhesion on various surfaces
Sound	Noiseless
Warranty	Positive printing   1 year
Recommended max. width printing	Tape width minus 3 mm
Colours	Reddish brown and white
Number of colours printed	Max. 5 colours and full colour
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	1-3 colours: 1 box = 30 rolls 4-5 colours: 8 boxes = 240 rolls

Technical Data	Unit	
Base		Polypropylene film, monoaxially oriented
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 160
Thickness	µm	77 ± 10%
Adhesion Strength	N/cm	2.8 ± 0.6
Thickness foil	µ	40

## Properties

- high tensile strength in longitudinal direction
- high adhesion on various surfaces
- low elongation
- sturdy backing
- excellent shock and impact strength
- resistant to diluted acids and alkalies
- heat resistant – short term up to approx. +100° C
- cold resistant – after application at room temperature down to -30° C

## Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%