

Characteristics

Low initial tack, full adhesion achieved after 24 hours.

Print 6-8 months preservable.

Suitable for frozen food packaging as long as processed above 0°C.

Data	
Adhesion	Low initial tack, full adhesion achieved after 24 hours
Sound	Low-noise*
Warranty	Positive printing 6 months
Recommended max. width printing	Tape width minus 3 mm
Colours	Clear, white, brown
Number of colours printed	Max. 5 colours
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	1-3 colours: 4 boxes = 144 rolls 4-5 colours: 8 boxes = 288 rolls

* Only on non-printed surface

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
	-	-	-	19	25	-	38	50	75	-	150		
PPA	-	-	-	19	25	-	38	50	75	-	150	990 mtr	5

Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Acrylic water-based
Elongation	%	150 \pm 10%
Thickness	μ m	654 \pm 10%
Adhesion to steel	N/cm	2.6 \pm 10%
Tensile strenght	N/cm	55 \pm 10%

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%