

### Characteristics

Good adhesion, suitable for frozen food packaging as long as processed above 5°C.

Data	
Adhesion	High initial tack
Sound	Noisy
Warranty	1 year
Max. width printing	Tape width
Colours	Clear, white, brown
Number of colours printed	Max. 8 colours and full colour
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	1-2 colours: 15 boxes = 540 rolls 3 colours: 33 boxes = 1188 rolls More colours: on request

Tape material	Tapewidth in mm. From ■ in maximum length possible												Max. length	Max. number of colours
	-	-	-	19	25	-	38	50	75	100	150			
PPH white	-	-	-	19	25	-	38	50	75	100	150		1500 mtr	8
PPH clear	-	-	-	19	25	-	38	50	75	100	150		990 mtr	8
PPH brown	-	-	-	19	25	-	38	50	75	100	150		990 mtr	8

## Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Synthetical Rubber Resin
Elongation	%	145
Thickness	$\mu\text{m}$	46 $\pm$ 10%
Adhesion to steel	N/cm	4.6 $\pm$ 10%
Tensile strenght	N/cm	49 $\pm$ 10%

## Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

## Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%