

## Characteristics

Suitable for frozen food packaging or rather cold environment as long as processed above 5°C  
 Suitable for boxes made from recycled paper

Data	
Adhesion	High initial tack and does not roll off too lightly
Sound	Noisy
Warranty	Positive printing 1 year
	All-over diapositive printed / coloured Due to risk of tearing warranty can not be given
Recommended max. width printing	Tape width minus 3 mm
Colours	White
Number of colours printed	Max. 5 colours and full colour
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	1-3 colours: 4 boxes = 120 rolls 4-5 colours / full colour: 8 boxes = 240 rolls

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
	-	-	-	19	25	-	38	50	75	-	150		
PPR	-	-	-	19	25	-	38	50	75	-	150	660 mtr	5

**Application**

For outer packaging, bandages as well as reinforcing of edges and angles we recommend PP Solvent 50μ

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 70
Thickness	μm	70 ± 10%
Adhesion Strength	N/cm	2.0 ± 0.6

**Properties**

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies (print can be effected)
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

**Storage conditions**

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%