

Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.

Data		
Adhesion	High initial tack and does not roll off too lightly	
Sound	Noiseless	
Warranty	Positive printing	1 year
	All-over diapositive printed / coloured	Due to risk of tearing warranty can not be given
Recommended max. width printing	Tape width minus 3 mm	
Colours	Clear, white, brown	
Number of colours printed	Max. 5 colours and full colour	
Core diameter	76 mm	
Minimum order (50 mm x 66 mtr)	1-3 colours: 1 box = 36 rolls 4-5 colours / full colour: 8 boxes = 288 rolls	

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
	9	12	15	19	25	30	38	50	75	100	150		
PVC				19								990 mtr	5

Application

PVC 32 μ has been developed as packaging tape for outer packaging of commercial cartons. Also large cartons and plastic containers can be reliably and securely sealed.

Technical Data	Unit	
Base		Rigid PVC film
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 36
Thickness	μm	$52 \pm 10\%$
Adhesion Strength	N/cm	2.0 ± 0.6

Properties

- high tensile strength and adhesion strength
- moisture resistant
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%