

Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.
Small details - grids may blur or dissappear.

Data	
Adhesion	High initial tack and does not roll off too lightly
Sound	Low-noise
Warranty	Product / material 6 months
	All-over diapositive printed / coloured Due to risk of tearing warranty can not be given
Recommended max. width printing	Tape width minus 3 mm
Colours	Brown
Number of colours printed	5 colours
Core diameter	76 mm
Minimum order (50 mm x 50 mtr)	36 rolls

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
Paper				19	25	30	38	50	75	-	150	500 mtr	5

Application

Paper 125μ is a self-adhesive packaging tape with a high tensile strength suitable for printing. The special adhesive and the thick backing material will ensure a reliable sealing of heavy cartons and pack lots.

Technical Data	Unit	
Base		Paper
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 35
Paper thickness	μm	± 90
Adhesive thickness	μm	± 25
Total thickness	μm	± 125
Adhesion Strength	N/cm	2.5 N/cm ± 0,6
Grammage	Gram	60 m ²

Properties

- high tensile strength and adhesion strength
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +60° C
- suitable for printing
- environmentally friendly, recyclable with cardboard
- printed with water based ink
- tearable by hand
- silicone free, free from synthetic plastics

Storage conditions

Store in a clean dry place. Temperature 15 - 23 degrees celcius.