2B2 Tape



Characteristics

Intended for closing PP and PE bags. Especially suitable in the food industry, packaging of bakery products, fruits and vegetables and similar. Close the bag with one movement, and because of the combination of paper and tape, it can easily be opened.

Data			
Adhesion	Н	High initial tack and does not roll off too lightly	
Sound		Noiseless	
Warranty	Positive printing	1 year	
Colours	Y	Yellow, red, green, blue, orange, fluor orange, brouwn, black, clear, white, white/white	
Number of colours printed		Max. 3 colours	
Minimum order (9 mm x 180 mtr)	unprinted: 1 box = 96 rolls printed with 1-3 colours: 4 boxes = 384 rolls		

Colours

The colours of coloured tape correspond approximately with the following PMS colours:

Yellow: Pantone 012c Orange: Pantone 158c Clear: Clear Red: Pantone 032c Fluor Orange: Pantone 811c White: Opaque white

Green: Pantone 361c Brown: Pantone 7504c White/white: White

Blue: Pantone 299c Black: Black

2B2 Tape

Application

PVC colored is particularly suitable for effectively marking goods for advertising purposes. It has an excellent adhesion to various surfaces. Printed PVC colored is often used for indication purposes.

Technical Data	Unit	
Base		Rigid PVC film
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 40
Thickness	μm	57 ± 10%
Adhesion Strength	N/cm	2.0 ± 0.6
Thickness foil	μ	37

Properties

- high tensile strength and adhesion strength
- moisture resistant
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature
- suitable for printing

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%