

### Characteristics

Low initial tack, full adhesion achieved after 24 hours.  
Suitable for frozen food packaging as long as processed above 0°C.

Data	
Adhesion	Low initial tack, full adhesion achieved after 24 hours
Sound	Low-noise
Warranty	1 year
Max. width printing	Tape width
Colours	Clear, white, brown
Number of colours printed	Max. 8 colours and full colour
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	1-2 colours: 15 boxes = 540 rolls 3 colours: 33 boxes = 1188 rolls More colours: on request

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
	-	-	-	19	25	-	38	50	75	-	150		
PPA	-	-	-	19	25	-	38	50	75	-	150	990 mtr	8

## Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Acrylic water-based
Elongation	%	150 $\pm$ 10%
Thickness	$\mu$ m	52 $\pm$ 10%
Adhesion to steel	N/cm	2.4 $\pm$ 10%
Tensile strenght	N/cm	59 $\pm$ 10%

## Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

## Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%