

## Characteristics

Good adhesion between 18-22 degrees. Not suitable for freezing or rather cold environment. Suitable for boxes made from recycled paper.

Data	
Adhesion	High initial tack and does not roll off too lightly
Sound	Noiseless
Warranty	Positive printing 1 year
	All-over diapositive printed / coloured Due to risk of tearing warranty can not be given
Recommended max. width printing	Tape width minus 3 mm
Colours	Yellow, red, green, blue, orange, fluor orange, black, white/white
Number of colours printed	Max. 5 colours and full colour*
Core diameter	76 mm
	1-3 colours: 1 box = 36 rolls 4-5 colours / full colour: 8 boxes = 288 rolls

\* Not all colors can be printed on colored PVC

Tape material	Tapewidth in mm. From ■ in maximum length possible												Max. length	Max. number of colours
PVC	9	12	15	19	25	30	38	50	75	-	150	200	990 mtr	5

## Colours

The colours of coloured tape correspond approximately with the following PMS colours:

Yellow: Pantone 012c	Orange: Pantone 158c
Red: Pantone 032c	Fluor Orange: Pantone 811c
Green: Pantone 361c	White/white: White
Blue: Pantone 299c	Black: Black



Application

PVC colored is particularly suitable for effectively marking goods for advertising purposes. It has an excellent adhesion to various surfaces. Printed PVC colored is often used for indication purposes.

Technical Data	Unit	
Base		Rigid PVC film
Adhesive		Natural rubber
Breaking Load	N/cm	minimum 40
Thickness	μm	57 ± 10%
Adhesion Strength	N/cm	2.0 ± 0.6

Properties

- high tensile strength and adhesion strength
- moisture resistant
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +70° C
- low temperature resistant down to about -20° C after application at room temperature
- suitable for printing

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%

