

### Characteristics

Low initial tack, full adhesion achieved after 24 hours.  
Suitable for frozen food packaging as long as processed above 0°C.

| Data                           |   |
|--------------------------------|---|
| Adhesion                       | Low initial tack, full adhesion achieved after 24 hours   |
| Sound                          | Low-noise   |
| Warranty                       | 1 year  |
| Max. width printing            | Tape width  |
| Colours                        | Clear, white, brown   |
| Number of colours printed      | Max. 8 colours and full colour  |
| Core diameter                  | 76 mm   |
| Minimum order (50 mm x 66 mtr) | 1-2 colours on white: 10 boxes = 360 rolls<br>1-2 colours on clear or brown: 15 boxes = 540 rolls<br>3 colours: 33 boxes = 1188 rolls. More colours: on request |

| Tape material | Tapewidth in mm. From ■ in maximum length possible |   |   |    |    |   |    |    |    |   |     | Max. length | Max. number of colours |
|---------------|--|---|---|----|----|---|----|----|----|---|-----|-------------|------------------------|
|               | -  | - | - | 19 | 25 | - | 38 | 50 | 75 | - | 150 |             |                        |
| PPA           | -  | - | - | 19 | 25 | - | 38 | 50 | 75 | - | 150 | 990 mtr     | 8                      |

## Application

| Technical Data    | Unit    |  |
|-------------------|---------|--|
| Base              |         | polypropylene film, biaxially oriented |
| Adhesive          |         | Acrylic water-based                    |
| Elongation        | %       | 145 $\pm$ 10%                          |
| Thickness         | $\mu$ m | 49 $\pm$ 10%                           |
| Adhesion to steel | N/cm    | 2.4 $\pm$ 10%                          |
| Tensile strenght  | N/cm    | 49 $\pm$ 10%                           |

## Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

## Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%