

Characteristics

Good adhesion, suitable for frozen food packaging as long as processed above 5°C.
Full-surface and reverse printing possible, but is not recommended.

Data	
Adhesion	High initial tack
Sound	Noisy
Warranty	Positive printing 6 months
	All-over diapositive printed / coloured Due to risk of tearing warranty can not be given
Recommended max. width printing	Tape width minus 3 mm
Colours	Clear, white, brown
Number of colours printed	Max. 5 colours and full colour
Core diameter	76 mm (also possible 3M core diameter 50 mm)
Minimum order (50 mm x 66 mtr)	1-3 colours: 4 boxes = 144 rolls 4-5 colours / full colour: 8 boxes = 288 rolls

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours
	-	-	-	19	25	-	38	50	75	100	150		
PPH	-	-	-	19	25	-	38	50	75	100	150	990 mtr	5



Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Synthetical Rubber Resin
Elongation at break	%	154
Thickness	μm	$57 \pm 10\%$
Adhesion to steel	N/cm	$5.0 \pm 10\%$
Tensile strenght	N/cm	$54 \pm 10\%$

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial

Storage conditions

Store in a clean dry place. Temperature 18 - 24 degrees celcius, and humidity of 40% - 50%